



PORTABLE FIRE EXTINGUISHERS

10 LB. CARBON DIOXIDE STORED PRESSURE FIRE EXTINGUISHER ARAMCO SPL MODEL

DESCRIPTION

Buckeye's 10 LB Carbon Dioxide Fire extinguisher is used on "B" and "C" class fires.

It is ideal for use in chemical and manufacturing plants, oil rigs, rail yards, warehouses, construction sites, parking garages, boat docks, and large laboratories.

FEATURES

- Manufactured in accordance with ANSI/UL 154 and ANSI/UL 711 Standards. USDOT compliant cylinders are tested to 3000 psi.
- US COAST GUARD approved for Type B:C Size I when used in conjunction with Mounting Bracket Model 810, P/N 700228.
- Polyester epoxy powder coated aluminum cylinder, rugged plated brass valve, and stainless steel handle and lever.
- Carbon Dioxide is a residue-free extinguishing agent that is environmentally friendly. Carbon Dioxide has an Ozone Depletion Potential (ODP) of 0 and a Global Warming Potential (GWP) of 1.
- Gold-plated Safety Burst Disc for added corrosion resistance

SPECIFICATIONS

Agent Capacity: 10 lbs. / 4.54 kg

UL Rating: 10-B:C

Shipping Weight: 27.75 lbs. / 12.6 kg

Height: 19.75 in / 50.2 cm

Width: 12.0 in / 30.5 cm

Cylinder Diameter: 6.89 in / 17.5 cm

Discharge Time: 9 seconds

Discharge Range: 4 – 8 ft / 1.2 – 2.4 m

Operating Temperature Range:
-22° F to 120° F / -30° C to 49° C

ORDERING INFORMATION

**10 LB Carbon Dioxide Fire
Extinguisher with Wall Hook**
P/N 45600SPL

Note: For Coast Guard Approval you must also order the Model 810 Mounting Bracket, P/N 700228

Refer to the Buckeye Spare Parts List for replacement parts