

## Technical Information

<b>Model</b>	<b>500 (Water)</b>	<b>WM250 (Water Mist)</b>
<b>Part #</b>	50000 (50000 ULC)	51000 (51000 ULC)
<b>Cylinder/Valve Material</b>	Stainless Steel/Plated Brass	Stainless Steel/Plated Brass
<b>Agent Capacity</b>	2.5 gallons (9.6 liters)	2.5 gallons (9.6 liters)
<b>UL/ULC Rating</b>	2-A	2-A:C
<b>Temperature Range</b>	40° to 120°F (4.4° to 49°C)	40° to 120°F (4.4° to 49°C)
<b>Discharge Time</b>	50 sec	73 sec
<b>Discharge Range</b>	45 to 55 ft. (13.7 to 16.8m)	5 to 10 ft. (1.5 to 3m)
<b>Operating Pressure</b>	100 psi (689 kPa)	100 psi (689 kPa)
<b>Mounting Type</b>	Wall	Wall
<b>USCG Approval</b>	Type A Size II	N/A
<b>Ship Weight</b>	Empty: 8.3 lb. (3.7 kg)	Full: 30.25 lb. (13.7 kg)
<b>Unit Height</b>	24.5 in (62.2 cm)	28 in (78.1 cm)
<b>Unit Width (Incl. Hose)</b>	9 in (22.9 cm)	14 in (35.6 cm)
<b>Unit Diameter</b>	7 in (17.8 cm)	7 in (17.8 cm)